



# ML910™

## Rugged Notebook



### KEY FEATURES

Magnesium alloy and plastic housing is fully sealed; meets rigorous environmental specs of MIL-STD-810F

Intel® Core™ Duo, 1.66GHz Processor

Fingerprint image reader provides convenience and security

Motorola's Advanced Dock Solution with hot-docking capability and automatic antenna switching

The full-sized, feature-rich ML910 Rugged Notebook features a sunlight readable, high resolution LCD Panel that provides high quality detailed graphical images on a 13.3" Touchscreen display.

Configurable Media Bay with numerous options.

The ML910 Rugged Notebook runs Windows® XP operating systems and supports a wide range of wireless options including

embedded EV-DO/1xRTT, embedded GPRS/EDGE/UMTS, Motorola DataTAC, 802.11abg, GPS and Bluetooth.

Innovative antenna design

Optimized thermal management solution

Field replaceable three dimensional shock absorber mounted hard drive with heater

With more than 75 years of technological innovations and over 30 years of wireless data expertise, Motorola has an answer for your mobile data needs.

Top to bottom, handle to hinge, the ML910 is Motorola-designed and developed for remarkable flexibility, versatility and durability. This ultra-robust, ruggedized notebook meets and exceeds MIL-STD 810F standards. Full-sized and full-featured, it is our most advanced rugged notebook computer, ready to handle the demands of the mission-critical world.

Experience Motorola quality and design with advanced features such as Intel Core Duo processor; shock mounted removable 80 GB hard drive with heater; high-resolution, glare-free WXGA (16:9)

screen; optional full-sized 13.3" touch display; Configurable Media Bay with optional: CD RW/DVD ROM, CD RW / DVD RW, Secondary Removable 8GB Solid State Drive, or Secondary Battery; fingerprint ID reader for added security; fully-sealed backlit keyboard; automatic GPS external antenna switching with advanced hot-dock solution; on-board digital video recorder.

For the most complete set of wireless options in a rugged design – choose the ML910 Rugged Notebook!

SPECIFICATION SHEET

ML910™  
Rugged Notebook

SYSTEM FUNCTION (ML910)

<b>CPU</b>	Intel® Core™ Duo L2400 2MB L2 1.66GHz 667MHz Processor
<b>Memory</b>	Standard: 512 MB Max 2GB (4GB planned, pending availability)
<b>Video Graphics Adapter</b>	ATIMobility Radeon™ X1400 (dedicated 128MB) MotionComp capability, support hardware aid for DVD playback Support Dual View function LCD/CRT simultaneous display capability
<b>Display</b>	13.3" transmissive WXGA (1280 x 800) LCD with touch screen 500+ NIT Brightness
<b>Hard Disk Drive</b>	80 GB standard shock-mounted w/ heater; Optional: 120 GB hard disk drive, 16GB Solid State Drive (SSD)
<b>Drive Bay</b>	Configurable Media Bay, Options: CD RW / DVD ROM (Combo Drive), CD RW/ DVD RW (Dual Drive), Secondary Battery, or Removable 8GB Secondary Solid State Drive (SSD).
<b>Floppy Disk Drive</b>	External USB floppy (optional)
<b>Keyboard</b>	Full travel QWERTY, fully-sealed backlight keyboard; rubberized backlight keyboard (optional)
<b>Pointing Device</b>	Touchpad with 4 programmable buttons
<b>Fingerprint Scanner</b>	500dpi (requires customer provided software application)
<b>PCMCIA</b>	1x External Type II - Cardbus support (Accessory PCMCIA to pci Express 34 converter card included)
<b>Audio</b>	AC97 Audio Support, MS-Sound Compatible High Definition Audio Codec (Azalia Compliant) Built-in speakers (stereo) Microphone In Port Earphone/Speaker Out Port/ S/PDIF Output Port
<b>I/O Port</b>	1x Serial 3x USB 2.0 1x RJ11 v.90/92 Modem 1x15 pin RGB External Monitor Output 1x Composite Analog Video Input Port 1x DC Input 1x Shrouded Hot-docking Port 1x RJ-45 10/100/1000 Base-TLAN 2x External RF Pass-Through Ports (1:GPS, 1:WWAN)
<b>Battery</b>	Smart Li-Ion 7200 mAh Secondary Battery (Media Bay Option) 3500 mAh
<b>AC Adapter</b>	Universal AC adapter – Input: 100-240 V, 50/60 Hz AC

PHYSICAL

<b>Dimensions</b>	3.2"x11.1"x13.2" (336mmx283mmx78mm)
<b>Weight</b>	9.8 lbs (4.5 kg)
<b>Operating System</b>	Supports Windows® XP, SP2



SPECIFICATION SHEET

ML910™  
Rugged Notebook

---

ENVIRONMENTAL STANDARDS (MAIN SYSTEM)

<b>Temperature</b>	According to IEC 68-2-1,2,14 / MIL-STD-810F, Method 501.4, 502.4 Operating: -20°C to 60°C (Tested)
<b>Humidity</b>	According to IEC 68-2-30 / MIL-STD-810F, Method 507.4 5% to 95% RH, non condensing
<b>Altitude</b>	According to IEC 68-2-30 / MIL-STD-810F, Method 500.4 Operating: 15,000 ft Non-operating: 40,000 ft altitude change rate: 2,000 ft/min
<b>Drip</b>	According to MIL-STD-810F, Method 506.4
<b>Shock</b>	According to IEC 68-2-27 / MIL-STD-810F, Method 516.5 Operating: 20g, 11 ms, half sine wave Non-operating: 50g, 11 ms, half sine wave
<b>Vibration</b>	According to IEC 68-2-6 / MIL-STD-810F, Method 514.5 Operating: 10~55Hz/0.075mm, 55~500Hz/1.0g Non-operating: 10~55Hz/0.15mm, 55~500Hz/2.0g
<b>Dust</b>	According to MIL-STD-810F, Method 510.4 5 hours in dust-laden atmosphere
<b>Drop</b>	According to IEC 68-2-32 / MIL-STD-810F, Method 516.5 (base unit only) Survives 30-36" drop depending on configuration
<b>Enclosure</b>	According to IEC 529, NEMA, MIL-STD-810F, Method 506.4, 510.4
<b>Regulatory</b>	FCC part 15, Subpart B, Class B, UL, CE, IC (targeted approvals)
<b>Integrated Wireless Communication Options</b>	1x Wide Area RF (Private DataTAC or EVDO (RevA)/1xRTT or GPRS/Edge/UMTS) (optional) 1x Wireless LAN (802.11abg with LEAP) Standard 1x Global Positioning System (GPS) receiver (Trimble Lassen iQ GPS Module) (optional) 1x Personal Area Network (Bluetooth) Standard RF Pass-through with external Antennas for Wide Area Network and GPS (optional) when Docked in High-Tier Docking Station
<b>Accessories and Options</b>	Primary and Secondary Batteries Office Port Replicator/Docking Station Vehicle Docking Station (High-Tier, Mid-Tier) External Mounted GPS and WWAN antennas DC 12V Cigarette Lighter Adapter USB Floppy Disk Drive (External) Configurable Media Bay Options: CD RW / DVD ROM (Combo Drive), CD RW/ DVD RW (Dual Drive), or Secondary Battery. PCMCIA Smart Card Reader PCMCIA Motorola Mesh Modems (WMC 6300,WMC 7300, WDE 1000) Mobile Office Display Solution (MODS: for functional dual display in-vehicle use) Travel Bags
<b>Warranty</b>	3 Year Full Warranty Standard (1 Year Consumables) Extended Service Plans Available

SPECIFICATION SHEET

ML910™  
Rugged Notebook



Motorola, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. [www.motorola.com/ML910](http://www.motorola.com/ML910) 1-800-367-2346

MOTOROLA, MOTOMESH, DataTAC and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. Intel® is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation; and Windows XP is a trademark of Microsoft Corporation. All other product or service names are the property of their registered owners. The Bluetooth trademarks are owned by their proprietor and used by Motorola, Inc. under license. © Motorola, Inc. 2007. All rights reserved.

R3-14-2050C (0712)